Sureflow SCA2

Anti-Scalant & Hard Water Protector

Industrial Water Systems

Application

Dissolved minerals such as calcium carbonate ($CaCO_3$) and magnesium carbonate ($MgCO_3$), precipitate out of system fluids and form scale deposits on the surface of the system's components, including pipes, boilers, and heat exchangers, leading to reduced efficiency and higher energy costs.

Sureflow SCA2 forms a stable complex with the inorganic minerals preventing them from precipitating out of solution and forming scale.

Additionally, Sureflow SCA2 can also help to disperse existing scale deposits, breaking them down into smaller particles that can be carried away by the water flow. This action helps to keep the system free from scale deposits that can reduce the efficiency of the system by insulating the heat transfer surfaces and reducing the flow of water.

Product Description

Sureflow SCA2 is a concentrated blend of anti-scale and sequestering agents, preventing mineral scale formation to maintain system efficiency.

Concentrated formulation for use in large industrial systems,

Benefits

- Concentrated formula
- Non toxic
- Easy to use
- Cost effective and long-life
- Compatible with most other treatments
- Improves system performance

Physical Properties

Appearance
Pale yellow liquid

Consistency
Low viscosity

Density
1.05 - 1.15

Odour
Slighy odour

Foam
Non-foaming

pH
7 - 8

Container Sizes
Available in: 5, 10, 25, 205L drums & 1000L IBCs

Hydratech Services Division

The Hydratech Services division provides specialist engineering and maintenance services to customers installing, commissioning, operating or optimising closed loop cooling and heating systems. Hydratech's holistic approach to process and hydronic systems management maximises the potential for optimised performance, reduced operational costs and significant return on investment gains.

Find out more about Hydratech Services

Quality Assured

Sureflow SCA2 is manufactured in accordance with ISO 9001: 2015 procedures.

Storage & Shelf Life

At least 3 years when stored in sealed containers, below 40°C and out of direct sunlight.

Health & Safety

Please refer to the associated Safety Data Sheet, which is available online via Login and/or by mail.

24/7 Technical Support

Technical support services and products to ensure ongoing system efficiency and protection.

tel. 01792 586800

sales@hydratech.co.uk

