



Bio-PG Antifreeze

For process cooling & AC systems

Performance Properties

Coolflow ECO3 has been especially formulated to provide Refrigeration and AC plant operators with a Secondary Refrigerant Antifreeze that is 100% renewable. I.e. not derived from non-renewable crude oil.

Non Toxic:

Coolflow ECO3 is based on sustainable Refined Vegetable Extracts that are Non Toxic.

Protection:

Coolflow ECO3 contains synergistic corrosion inhibitors to protect metals commonly found in such systems. It has been tested in accordance with BS5117 and found to meet BS6580 and ASTM D1384 corrosion standards.

Coolflow ECO3 also contains scale and biological inhibitors to help prevent fouling - thus promoting long operational life and high thermal efficiency.

Application

As per BSRIA guide BG 29/2012 all pipe-work systems should be clean and free from biological contamination and debris prior to commissioning.

To minimise corrosion air ingress should be minimised. A pressurised system is best.

Determine the total system volume and add **Coolflow ECO3** to the system according to the minimum operating temperature required (see table, below). The minimum dose of **Coolflow ECO3** should not be less than 25% of the system volume and the maximum does not normally exceed 60%. We recommend the use of deionised, distilled or UltraPure™ water for this dilution. Avoid water containing high levels of calcium salts or Chlorides [Cl-].

Coolflow ECO3 can also be supplied as a Ready-To-Use solution.

Physical Properties

Frost Protection

-50°C depending on concentration.

Density

1.02 - 1.26 g/cm³

pH

7.5 - 9.0 depending on inhibitors

Boiling Point

>100°C

For operating temperatures above 100°C, refer to Hydratech for technical advice.

Characteristics

a clear, slightly viscous liquid. It is slightly sweet to the taste and has a non-pungent but characteristic aroma.

Biodegradability

Coolflow ECO3 is capable of being decomposed in to its constituent elements by natural processes. I.E. The product will not remain in the environment after it has been broken down. The approximate time of decomposition is detailed in the product Safety Data Sheet.

Container Sizes

Available in: 5, 10, 25, 205L drums & 1000L IBCs



www.hydratech.co.uk | sales@hydratech.co.uk

Fluid Management Services

To ensure inhibitor levels are being maintained and the system fluid is in good condition, we recommend periodic sampling and testing. Hydratech operate the Fluid Monitoring Program (FMP) service for all users of our products. For more information on the FMP please call or visit www.hydratech.co.uk.

Quality Assured

Coolflow ECO3 meets or exceeds the corrosion standards laid down in ASTM D-1384. Hydratech products are manufactured in accordance with ISO 9001: 2015 procedures.

Storage & Shelf Life

At least 3 years when stored in sealed containers, below 40°C and out of direct sunlight.

Health & Safety

Please refer to the associated Safety Data Sheet, which is available online via Login and/or by mail.

24/7 Technical Support

Technical support services and products to ensure ongoing system efficiency and protection.

tel. 01792 586800

sales@hydratech.co.uk

